

QN0805X334J3950FB

R25=330kΩ±5%， B25/50=3950±1%， B25/85=4010

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
-40	9,766.852	10,644.298	11,571.572	8.71%	1.27
-39	9,160.486	9,976.995	10,839.117	8.64%	1.27
-38	8,595.340	9,355.457	10,157.335	8.57%	1.27
-37	8,068.387	8,776.293	9,522.443	8.50%	1.27
-36	7,576.837	8,236.383	8,930.958	8.43%	1.27
-35	7,118.116	7,732.852	8,379.677	8.36%	1.27
-34	6,689.853	7,263.050	7,865.646	8.30%	1.27
-33	6,289.861	6,824.534	7,386.146	8.23%	1.27
-32	5,916.118	6,415.051	6,938.671	8.16%	1.27
-31	5,566.761	6,032.520	6,520.906	8.10%	1.27
-30	5,240.065	5,675.022	6,130.719	8.03%	1.27
-29	4,934.438	5,340.783	5,766.140	7.96%	1.26
-28	4,648.407	5,028.165	5,425.350	7.90%	1.26
-27	4,380.611	4,735.652	5,106.669	7.83%	1.26
-26	4,129.789	4,461.842	4,808.543	7.77%	1.26
-25	3,894.773	4,205.441	4,529.537	7.71%	1.26
-24	3,674.483	3,965.247	4,268.321	7.64%	1.26
-23	3,467.918	3,740.149	4,023.666	7.58%	1.26
-22	3,274.148	3,529.119	3,794.435	7.52%	1.26
-21	3,092.314	3,331.201	3,579.571	7.46%	1.25
-20	2,921.616	3,145.512	3,378.099	7.39%	1.25
-19	2,761.314	2,971.231	3,189.113	7.33%	1.25
-18	2,610.718	2,807.596	3,011.772	7.27%	1.25
-17	2,469.191	2,653.901	2,845.298	7.21%	1.25
-16	2,336.137	2,509.490	2,688.967	7.15%	1.25
-15	2,211.006	2,373.753	2,542.108	7.09%	1.24
-14	2,093.283	2,246.123	2,404.097	7.03%	1.24

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
-13	1,982.491	2,126.074	2,274.355	6.97%	1.24
-12	1,878.187	2,013.115	2,152.343	6.92%	1.24
-11	1,779.955	1,906.792	2,037.560	6.86%	1.24
-10	1,687.411	1,806.678	1,929.540	6.80%	1.24
-9	1,600.195	1,712.381	1,827.850	6.74%	1.23
-8	1,517.974	1,623.530	1,732.085	6.69%	1.23
-7	1,440.436	1,539.784	1,641.869	6.63%	1.23
-6	1,367.289	1,460.823	1,556.853	6.57%	1.23
-5	1,298.262	1,386.348	1,476.710	6.52%	1.23
-4	1,233.102	1,316.082	1,401.135	6.46%	1.22
-3	1,171.572	1,249.765	1,329.844	6.41%	1.22
-2	1,113.451	1,187.155	1,262.574	6.35%	1.22
-1	1,058.534	1,128.026	1,199.075	6.30%	1.22
0	1,006.626	1,072.166	1,139.118	6.24%	1.21
1	957.549	1,019.378	1,082.488	6.19%	1.21
2	911.132	969.478	1,028.981	6.14%	1.21
3	867.219	922.292	978.411	6.08%	1.21
4	825.661	877.660	930.602	6.03%	1.20
5	786.321	835.430	885.387	5.98%	1.20
6	749.068	795.461	842.615	5.93%	1.20
7	713.782	757.620	802.140	5.88%	1.20
8	680.349	721.784	763.828	5.82%	1.19
9	648.662	687.836	727.551	5.77%	1.19
10	618.621	655.667	693.193	5.72%	1.19
11	590.133	625.175	660.641	5.67%	1.18
12	563.110	596.264	629.792	5.62%	1.18
13	537.468	568.845	600.548	5.57%	1.18
14	513.131	542.832	572.818	5.52%	1.18
15	490.025	518.148	546.516	5.47%	1.17
16	468.082	494.717	521.561	5.43%	1.17

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
17	447.239	472.470	497.878	5.38%	1.17
18	427.434	451.341	475.395	5.33%	1.16
19	408.610	431.269	454.046	5.28%	1.16
20	390.715	412.195	433.768	5.23%	1.16
21	373.698	394.064	414.502	5.19%	1.15
22	357.511	376.827	396.193	5.14%	1.15
23	342.110	360.433	378.789	5.09%	1.15
24	327.453	344.839	362.240	5.05%	1.14
25	313.500	330.000	346.500	5.00%	1.14
26	299.952	315.877	331.816	5.05%	1.16
27	287.060	302.432	317.831	5.09%	1.18
28	274.788	289.629	304.507	5.14%	1.19
29	263.105	277.434	291.811	5.18%	1.21
30	251.979	265.815	279.710	5.23%	1.23
31	241.380	254.743	268.173	5.27%	1.25
32	231.282	244.188	257.171	5.32%	1.26
33	221.657	234.126	246.677	5.36%	1.28
34	212.483	224.529	236.665	5.41%	1.30
35	203.735	215.375	227.111	5.45%	1.32
36	195.392	206.640	217.991	5.49%	1.34
37	187.432	198.305	209.283	5.54%	1.36
38	179.838	190.348	200.968	5.58%	1.38
39	172.589	182.750	193.025	5.62%	1.39
40	165.670	175.494	185.436	5.67%	1.41
41	159.062	168.563	178.184	5.71%	1.43
42	152.752	161.940	171.252	5.75%	1.45
43	146.723	155.611	164.624	5.79%	1.47
44	140.963	149.561	158.287	5.83%	1.49
45	135.457	143.776	152.224	5.88%	1.51
46	130.194	138.244	146.425	5.92%	1.53

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
47	125.162	132.953	140.875	5.96%	1.55
48	120.349	127.890	135.563	6.00%	1.57
49	115.745	123.045	130.478	6.04%	1.59
50	111.340	118.408	125.609	6.08%	1.61
51	107.125	113.968	120.946	6.12%	1.63
52	103.089	109.717	116.478	6.16%	1.65
53	99.226	105.645	112.198	6.20%	1.67
54	95.526	101.744	108.096	6.24%	1.69
55	91.983	98.007	104.164	6.28%	1.71
56	88.588	94.425	100.394	6.32%	1.73
57	85.335	90.991	96.780	6.36%	1.75
58	82.217	87.699	93.313	6.40%	1.77
59	79.229	84.542	89.987	6.44%	1.79
60	76.363	81.514	86.795	6.48%	1.81
61	73.615	78.609	83.733	6.52%	1.83
62	70.979	75.822	80.793	6.56%	1.85
63	68.451	73.147	77.970	6.59%	1.88
64	66.024	70.579	75.260	6.63%	1.90
65	63.695	68.114	72.657	6.67%	1.92
66	61.460	65.747	70.157	6.71%	1.94
67	59.313	63.473	67.754	6.75%	1.96
68	57.252	61.288	65.445	6.78%	1.98
69	55.272	59.190	63.226	6.82%	2.00
70	53.370	57.173	61.093	6.86%	2.03
71	51.543	55.234	59.042	6.89%	2.05
72	49.787	53.370	57.069	6.93%	2.07
73	48.098	51.578	55.172	6.97%	2.09
74	46.476	49.855	53.347	7.00%	2.11
75	44.915	48.197	51.590	7.04%	2.14
76	43.414	46.602	49.900	7.08%	2.16

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
77	41.971	45.068	48.273	7.11%	2.18
78	40.582	43.591	46.707	7.15%	2.20
79	39.245	42.169	45.198	7.18%	2.23
80	37.959	40.801	43.746	7.22%	2.25
81	36.721	39.483	42.347	7.25%	2.27
82	35.529	38.214	40.999	7.29%	2.30
83	34.381	36.991	39.700	7.32%	2.32
84	33.276	35.814	38.449	7.36%	2.34
85	32.211	34.679	37.243	7.39%	2.36
86	31.185	33.585	36.080	7.43%	2.39
87	30.197	32.531	34.958	7.46%	2.41
88	29.244	31.515	33.877	7.50%	2.44
89	28.326	30.535	32.834	7.53%	2.46
90	27.441	29.590	31.828	7.56%	2.48
91	26.587	28.679	30.858	7.60%	2.51
92	25.764	27.800	29.921	7.63%	2.53
93	24.971	26.952	29.017	7.66%	2.55
94	24.205	26.133	28.145	7.70%	2.58
95	23.466	25.343	27.302	7.73%	2.60
96	22.753	24.581	26.489	7.76%	2.63
97	22.065	23.845	25.703	7.80%	2.65
98	21.401	23.134	24.945	7.83%	2.68
99	20.760	22.448	24.212	7.86%	2.70
100	20.140	21.785	23.504	7.89%	2.73
101	19.543	21.144	22.820	7.93%	2.75
102	18.965	20.525	22.159	7.96%	2.78
103	18.407	19.928	21.520	7.99%	2.80
104	17.868	19.350	20.902	8.02%	2.83
105	17.347	18.791	20.304	8.05%	2.85
106	16.844	18.251	19.727	8.08%	2.88

温度 Temp. (°C)	R 最小值 R_Min (Kohm)	R 中心值 R_Cent (Kohm)	R 最大值 R_Max (Kohm)	阻值公差 Res TOL.	温度公差 Temp. TOL.(°C)
107	16.358	17.729	19.168	8.12%	2.90
108	15.887	17.225	18.628	8.15%	2.93
109	15.433	16.736	18.105	8.18%	2.95
110	14.993	16.264	17.599	8.21%	2.98
111	14.568	15.807	17.110	8.24%	3.00
112	14.156	15.365	16.636	8.27%	3.03
113	13.758	14.938	16.178	8.30%	3.06
114	13.373	14.524	15.734	8.33%	3.08
115	13.001	14.123	15.304	8.36%	3.11
116	12.640	13.735	14.888	8.39%	3.14
117	12.291	13.360	14.485	8.42%	3.16
118	11.953	12.996	14.094	8.45%	3.19
119	11.626	12.644	13.716	8.48%	3.21
120	11.309	12.303	13.350	8.51%	3.24
121	11.003	11.972	12.995	8.54%	3.27
122	10.705	11.652	12.651	8.57%	3.30
123	10.418	11.342	12.317	8.60%	3.32
124	10.139	11.041	11.994	8.63%	3.35
125	9.868	10.750	11.680	8.66%	3.38